

GANSKA-100

LED A A+ A++



FIXED

IP20



RAL Code

0,80




CRI>80

CRI>90



CLASS II



 220-240V AC

Extruded aluminium body with electrostatic powder coated,
High efficiency reflector and PC glass,
Effective thermal design,
50.000 hours Led lifetime,
Narrow, medium and wide beam angle options,
Emergency kit system can be integrated,
Please inquire for optional power values.

*Elektrostatik toz boyalı alüminyum ekstrüzyon gövde,
Yüksek verimli reflektör ve PC cam,
Etkili termal tasarım,
50.000 saat Led yaşam ömrü,
Dar, orta ve geniş açı seçenekleri,
Acil aydınlatma kit sistemi uygulanabilir,
Opsiyonel güç değerleri için bizimle iletişime geçebilirsiniz.*

Consuming Power Tüketim Gücü	20W (L: 183mm)	28W (L: 213mm)
Light Source Işık Kaynağı	COB LED	
Color Temperature Renk Sıcaklığı	2700K 3000K 4000K	5000K 6500K
Luminaire Output Lumen Armatür Çıkış Akısı	2090lm	2940lm
Efficiency Verimlilik	105lm/W	
Power Factor Güç Faktörü	Pf>90	
Forward Current Sürüş Akımı	500mA	700mA

