

# LAGRA

LED A A+ A++






350°

90°

1,30  
KG

CRI>80

CRI>90



IP40



RAL Code

F

CLASS II

220-240V  
AC

Die-cast aluminium body with electrostatic powder coated,  
High efficiency reflector and PC glass,  
Effective thermal design,  
50.000 hours Led lifetime,  
Compatible with Monophase or Triphase rail system,  
Narrow, medium and wide beam angle options,  
Please inquire for optional power values.

*Elektrostatik toz boyalı alüminyum döküm gövde,  
Yüksek verimli reflektör ve PC cam,  
Etkili termal tasarım,  
50.000 saat Led yaşam ömrü,  
Monofaze ve Trifaze ray sistemleriyle uyumlu,  
Dar, orta ve geniş açı seçenekleri,  
Opsiyonel güç değerleri için bizimle iletişime geçebilirsiniz.*

Consuming Power Tüketim Gücü	20W	28W	35W
Light Source Işık Kaynağı	COB LED		
Color Temperature Renk Sıcaklığı	2700K 3000K 4000K	5000K 6500K	
Luminaire Output Lumen Armatür Çıkış Akısı	2100lm	2940lm	3675lm
Efficiency Verimlilik	105lm/W		
Power Factor Güç Faktörü	Pf>90		
Forward Current Sürüş Akımı	500mA	700mA	900mA

