

LINA 5

LED A A+ A++



FIXED

IP20

RAL Code

0,42




KG

F


CRI>80

CRI>90

CLASS II



220-240V AC



Extruded aluminium body with electrostatic powder coated,
High efficiency optic in metallized thermoplastic and
built into the innovative anti-glare screen,
Effective thermal design,
50.000 hours Led lifetime,
Narrow, medium, wide and elliptical beam angle options,
Please inquire for optional power values.

*Elektrostatik toz boyalı alüminyum ekstrüzyon gövde,
Yüksek verimli metalik termoplastik optik ve kamaşma önleyici ekran,
Etkili termal tasarım,
50.000 saat Led yaşam ömrü,
Dar, orta, geniş ve eliptik açı seçenekleri,
Opsiyonel güç değerleri için bizimle iletişime geçebilirsiniz.*

Consuming Power

Tüketim Gücü

12W

Light Source

Işık Kaynağı

POWER LED

Color Temperature

Renk Sıcaklığı

2700K 5000K
3000K 6500K
4000K

Luminaire Output Lumen

Armatür Çıkış Akısı

936lm

Efficiency

Verimlilik

78lm/W

Power Factor

Güç Faktörü

Pf>90

Forward Current

Sürüş Akımı

500mA

