







RAL Code

ADJUSTABLE



CRI>80

CRI>90



IP20

F

CLASS II

220-240V AC

DALI  
switchDIM

Extruded aluminium body with electrostatic powder coated,  
High efficiency reflector and PC glass,  
Effective thermal design,  
50.000 hours Led lifetime,  
Narrow, medium and wide beam angle options,  
Emergency kit system can be integrated,  
Please inquire for optional power values.

Elektrostatik toz boyalı alüminyum ekstrüzyon gövde,  
Yüksek verimli reflektör ve PC cam,  
Etkili termal tasarım,  
50.000 saat Led yaşam ömrü,  
Dar, orta ve geniş açı seçenekleri,  
Acil aydınlatma kit sistemi uygulanabilir,  
Opsiyonel güç değerleri için bizimle iletişime geçebilirsiniz

Consuming Power Tüketim Gücü	7W	9W	14W
Light Source Işık Kaynağı	COB LED		
Color Temperature Renk Sıcaklığı	2700K 3000K 4000K	5000K 6500K	
Luminaire Output Lumen* Armatür Çıkış Akısı	721 lm	927 lm	1442 lm
Efficiency Verimlilik	103 lm/W		
Power Factor Güç Faktörü	Pf>90		
Weight Ağırlık	0.8 kg		

\* Lümen değeri 4000K değerine göre verilmiştir.  
Lumen value is given according to 4000K value.

