

LOVA BAKERY

LED A A+ A++



RAL Code

Die-cast aluminium body with electrostatic powder coated,
High efficiency reflector and PC glass,
Effective thermal design,
50.000 hours Led lifetime,
Compatible Triphase rail system,
Minimal apperance with Compact Track Adaptor Driver,
Narrow, medium and wide beam angle options,
Please inquire for optional power values.

*Elektrostatik toz boyalı alüminyum döküm gövde,
Yüksek verimli reflektör ve PC cam,
Etkili termal tasarım,
50.000 saat Led yaşam ömrü,
Trifaze ray sistemleriyle uyumlu,
Kompakt Ray adaptörlü sürücü ile minimal görünüm,
Dar, orta ve geniş açı seçenekleri,
Opsiyonel güç değerleri için bizimle iletişime geçebilirsiniz.*

Consuming Power Tüketim Gücü	20W	28W	35W
Light Source Işık Kaynağı	COB LED		
Color Temperature Renk Sıcaklığı	Enhanced whiteness and vividness by diminishing of yellowish		
Luminaire Output Lumen* Armatür Çıkış Akısı	1620 lm	2268 lm	2835 lm
Efficiency Verimlilik	81 lm/W		
Power Factor Güç Faktörü	Pf>90		
Weight Ağırlık	1.2 kg		


* Lümen değeri 2700K değerine göre verilmiştir.
Lumen value is given according to 2700K value.

ADJUSTABLE

350°

90°

CRI>90



IP40

F

CLASS II

220-240V
AC

DALI

switchDIM

