

STARK TRIO LB

LED A A+ A++



MAT Eloksal

Extruded aluminium body with electrostatic powder coated,
High efficiency reflector and extra clear tempered glass,
Effective thermal design,
50.000 hours Led lifetime,
Narrow, medium and wide beam angle options,
Emergency kit system can be integrated,
Please inquire for optionzal power values.

Elektrostatik toz boyalı alüminyum ekstrüzyon gövde,
Yüksek verimli reflektör ve extra clear temperli cam,
Etkili termal tasarım,
50.000 saat Led yaşam ömrü,
Dar, orta ve geniş açı seçenekleri,
Acil aydınlatma kit sistemi uygulanabilir,
Opsiyonel güç değerleri için bizimle iletişime geçebilirsiniz.

Consuming Power Tüketim Gücü	3X110W L: 490 mm	3X125W L: 490 mm	3x145W L: 560mm	3x200W L: 770mm
Light Source Işık Kaynağı	MP LED			
Color Temperature Renk Sıcaklığı	2700K 3000K	5000K 6500K		
Luminaire Output Lumen* Armatür Çıkış Akısı	44880 lm	51000 lm	59160 lm	81600 lm
Efficiency Verimlilik	136 lm/W			
Power Factor Güç Faktörü	Pf>90			
Weight Ağırlık	16.5 kg	16.5 kg	21.3 kg	22.8 kg

* Lümen değeri 5000K değerine göre verilmiştir.
Lumen value is given according to 5000K value.

FIXED

IP65

F

CLASS I

220-240V
AC

CRI>80 CRI>90

